

XXXZA (vehicle grade)

10D Series (车规级)

型号	标称压敏电压 (@ 1mA DC)	最大連續工作電壓		最大限制電壓		最大沖擊 電流	最大能量	額定功率	參考電容	厚度
	V _{1mA} (V)	VAC(rms) (V)	VDC (V)	Vp (V)	IP (A)	I _{max} (A)	W _{max} (J)	P (W)	C (pF)	T _{max} (mm)
SVR10D201K*78*HXXXZA	200	130	170	340	25	3500	35	0.4	500	5.9
SVR10D221K*78*HXXXZA	220	140	180	360	25	3500	39	0.4	450	5.9
SVR10D241K*78*HXXXZA	240	150	200	395	25	3500	42	0.4	420	6.0
SVR10D271K*78*HXXXZA	270	175	225	455	25	3500	49	0.4	370	6.2
SVR10D301K*78*HXXXZA	300	190	250	500	25	3500	54	0.4	330	6.3
SVR10D331K*78*HXXXZA	330	210	275	550	25	3500	58	0.4	300	6.6
SVR10D361K*78*HXXXZA	360	230	300	595	25	3500	65	0.4	280	6.7
SVR10D391K*78*HXXXZA	390	250	320	650	25	3500	70	0.4	260	6.8
SVR10D431K*78*HXXXZA	430	275	350	710	25	3500	80	0.4	230	7.2
SVR10D471K*78*HXXXZA	470	300	385	775	25	3500	85	0.4	210	7.5

SVR10D511K*78*HXXXZA	510	320	415	845	25	3500	90	0.4	200	7.5
SVR10D561K*78*HXXXZA	560	350	460	925	25	3500	92	0.4	180	7.5
SVR10D621K*78*HXXXZA	620	385	505	1025	25	3500	95	0.4	160	8.1
SVR10D681K*78*HXXXZA	680	420	560	1120	25	3500	98	0.4	150	8.4
SVR10D751K*78*HXXXZA	750	460	615	1240	25	3500	100	0.4	130	8.8
SVR10D781K*78*HXXXZA	780	485	640	1290	25	3500	105	0.4	125	8.9
SVR10D821K*78*HXXXZA	820	510	670	1355	25	3500	110	0.4	120	9.1
SVR10D911K*78*HXXXZA	910	550	745	1500	25	3500	130	0.4	110	9.6
SVR10D102K*78*HXXXZA	1000	625	825	1650	25	3500	140	0.4	100	10.1
SVR10D112K*78*HXXXZA	1100	680	895	1815	25	3500	155	0.4	90	10.7

PS: "*" Said Lead Style and Packing type

XXXZA(车规级)

14D Series (车规级)

型号	标称压敏电压 (@ 1mA DC)	最大連續工作電壓		最大限制電壓		最大沖擊 電流	最大能量	額定功率	參考電容	厚度
	V _{1mA} (V)	VAC(rms) (V)	VDC (V)	Vp (V)	IP (A)	I _{max} (A)	W _{max} (J)	P (W)	C (pF)	T _{max} (mm)
SVR14D201K*78*HXXXZA	200	130	170	340	50	6000	70	0.60	1000	5.9
SVR14D221K*78*HXXXZA	220	140	180	360	50	6000	78	0.60	900	5.9
SVR14D241K*78*HXXXZA	240	150	200	395	50	6000	84	0.60	830	6.0
SVR14D271K*78*HXXXZA	270	175	225	455	50	6000	99	0.60	740	6.2
SVR14D301K*78*HXXXZA	300	190	250	500	50	6000	108	0.60	670	6.3
SVR14D331K*78*HXXXZA	330	210	275	550	50	6000	115	0.60	610	6.6
SVR14D361K*78*HXXXZA	360	230	300	595	50	6000	130	0.60	560	6.7
SVR14D391K*78*HXXXZA	390	250	320	650	50	6000	140	0.60	510	6.8
SVR14D431K*78*HXXXZA	430	275	350	710	50	6000	155	0.60	460	7.2
SVR14D471K*78*HXXXZA	470	300	385	775	50	6000	175	0.60	430	7.5
SVR14D511K*78*HXXXZA	510	320	415	845	50	6000	180	0.60	390	7.5
SVR14D561K*78*HXXXZA	560	350	460	925	50	6000	185	0.60	360	7.5
SVR14D621K*78*HXXXZA	620	385	505	1025	50	6000	190	0.60	320	8.1
SVR14D681K*78*HXXXZA	680	420	560	1120	50	6000	200	0.60	290	8.4

SVR14D751K*78*HXXXZA	750	460	615	1240	50	6000	210	0.60	270	8.8
SVR14D781K*78*HXXXZA	780	485	640	1290	50	6000	220	0.60	260	8.9
SVR14D821K*78*HXXXZA	820	510	670	1355	50	6000	235	0.60	240	9.1
SVR14D911K*78*HXXXZA	910	550	745	1500	50	6000	255	0.60	220	9.6
SVR14D102K*78*HXXXZA	1000	625	825	1650	50	6000	280	0.60	200	10.1
SVR14D112K*78*HXXXZA	1100	680	895	1815	50	6000	310	0.60	180	10.7
SVR14D182K*78*HXXXZA	1800	1000	1465	2970	50	6000	335	0.60	130	15.4

PS: "*" Said Lead Style and Packing type